

## 5MP VF Motorized IR Bullet Network Camera

WIP540VMD



### Key Features



High quality image with 5MP, 1/2.7"CMOS sensor

5MP (2592\*1944) @25/20fps ; 4MP(2592x1520)@25/20fps; 3MP (2304\*1296) @25/20fps ; 2MP (1920\*1080) @30/25fps

H.265, H.264

Smart IR, up to 45m IR distance

Day/night functionality

Digital Wide Dynamic Range

3D DNR (Digital Noise Reduction)

Protection IP67

DC12V or PoE (IEEE 802.3af) power supply

## Specifications

Model Name	WIP540VMD
<b>Vidéo</b>	
Imaging Device	1/2.7"
Effective Pixels	5MP 2592(H)×1944(V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.004Lux @ (F1.6, AGC ON) ; B/W 0 lux @ IR ON
<b>Lens Type</b>	
Focal Length (Zoom Ratio)	2.7-13.5 mm
Max. Aperture Ratio	F No. 1.8 (W) ~ 3.3(T)
Angular Field of View	Horizontal: 31 ~102°, Vertical: 23 ~ 73°, Diagonal: 38 ~ 138°
Min. Object Distance	0.3m~INF
Lens Type	Motorized(Ø14)
<b>Operational</b>	
IR Viewable Length	Up to 45m
Camera Title	On/Off
Day & Night	IR cut filter with auto switch (Day/Night/Auto/Image/Schedule)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	NA
Audio	1 input (RCA), 1 output (RCA)
Hardware Reset	Yes
Smart Feature	NA
<b>Network</b>	
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	<p><b>Main Stream</b> 5MP(2592*1944)@20fps,4MP(2592x1520)@25fps,3MP(2304x1296),@30fps s1080P(1920x1080)@30fps960P(1280x960)@30fps720P(1280x720)@30fps</p> <p><b>Sub Stream @20fps</b> 720P(1280x720),VGA(640x480),QVGA(320x240)</p> <p><b>Mobile Stream @20fps</b> QVGA (320x240)</p>
Video Quality Adjustment	256Kbps ~ 8Mbps

Bitrate control method	CBR/VBR
Streaming Capability	Triple-Stream(Main/Sub/Moile)
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Web Browser	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
Security	complicated password;Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF ( Profile S/G/T)
Web Viewer	IE10/11
<b>Environmental</b>	
Operating Conditions	-35 ~ +60°C/less than ≤ 90% RH
Ingress Protection	IP67
<b>Electrical</b>	
Input Voltage / Current	D12V/POE(IEEE802.3af)
Power Consumption (IR OFF)	2W-3W
Power Consumption (IR ON)	7W-9W
<b>Mechanical</b>	
Material	Metal
Dimensions (HxWxD)	242*87/4*83..88mm
Weight	792g

## Dimensions

